

## Product Data Sheet

### Flowmaster MK2 System

**A multi-line admixture metering system  
for integration with plant computers**

#### Pumping / Metering Cabinet

- The Flowmaster range of pump cabinets can be configured to handle up to six admixtures. Their flexible design enables customers to expand the system if additional admixtures are required in the future.
- Flowmaster products only use MONO MS or MM range PD pumps. MONO pumps are extremely hard wearing and reliable. Flow rates vary from the MS pump at 13ltr per min to the MM at 26ltr per min.
- Supply voltages available 110v, 240v or 415v.
- Each admixture line incorporates an ABB "HS" type electronic flow meter with nickel chrome body and plastic / stainless internals (100 pulses per litre of admixture).
- Also incorporated are electronic flow indicators to enable your computer to detect if the admixture inlet line is primed or not.
- The main pump cabinet contains the admixture pumps, flow meters and flow switches which are protected by a panel heater and thermostat. A strip light is included to make servicing easier in bad lighting conditions.
- The smaller secondary panel contains a master isolator together with a set of secondary isolators to isolate individual pumps. This panel also houses the terminal rails and control gear.



**Recommended for use with;**

**BASFORD, COMMAND ALKON, DORNER, PRACTICON & SKAKO  
COMPUTER SYSTEMS.**

**For further information call +44 (0) 1942722677  
or**

**Visit our web site [www.norstrom.co.uk](http://www.norstrom.co.uk)**