

## The **NEW** Proflush Combo HI-98129



### Combined Meter pH / Conductivity / TDS / °C

The **Combo** HI-98129 waterproof testers are designed for high accuracy pH / Conductivity / TDS / temperature measurements.

- No more switching between meters, the **Combo** is capable of reading pH and EC/ TDS. All readings are automatically temperature compensated for (ATC).
- The **Combo** has a selectable EC / TDS conversion factor and temperature compensation coefficient.
- The **Combo** is waterproof and will float. It has a large easy to read dual level LCD with an automatic power cut off.
- The **Combo** has a replaceable pH electrode cartridge with a cloth removable junction as well as an EC / TDS graphite electrode which resists contamination by salts and other substances.
- Fast, efficient, accurate and portable the **Combo** meets the requirements of multi routine measurements.

**For more information Contact Terry Dyson on 01942 722677**

## The **NEW** Proflush TDS 3 Pocket Tester with ATC



### Pocket Tester for TDS (Total Dissolved Solids)

#### **FEATURES**

Ideal for commercial use. Includes a carrying case with belt clip.

Highly efficient and accurate due to its advanced microprocessor technology.

Hold Function: saves measurements for convenient reading and recording.

Auto-off function: the meter shuts off automatically after 10 minutes of non-use to conserve batteries.

Measurement Range: 0-9990ppm. From 0-999ppm, the resolution is in increments of 1ppm. From 1,000 to 9,990ppm, the resolution is in increments of 10ppm, indicated by a blinking 'x10' image.

Display: large and easy-to-read LCD screen.

Factory calibrated: recalibration is not necessary, but can be done easily with a watch screwdriver. There's no need for messy solutions.

*Also available in "x10" mode: reads in increments only of 10ppm (0-9990ppm).*

#### **SPECIFICATIONS**

Range: 0 - 9990ppm (mg/L)

Accuracy: +/- 2%

ATC: Built-in sensor for Automatic Temperature Compensation of 1 to 50 degrees Celsius (33 to 122 degrees Fahrenheit)

Power source: 2 x 1.5V button cell batteries (included)

Battery life: over 1,000 hours of continuous use

Dimensions: 15.5 x 3.1 x 2.3cm (6.1 x 1.25 x 1 inches)

Weight with case: 76.5g (2.7 oz)

Weight without case: 56.7g (2 oz)

**For more information Contact Terry Dyson on 01942 722677**